

# ABRASAPIPE®

## WELD OVERLAY WEAR PIPE

www.avweld.com.au | sales@avweld.com  
 25 Raymond Road, Laverton North, VIC, 3026  
 Phone (03) 9369 0088

AbrasaPipe® is chrome carbide weld-overlay wear pipe. The high hardness of the weld overlay make its suitable for abrasion resistant applications, such as transport of slurries, abrasive minerals and dust.

AbrasaPipe® features significantly better abrasion resistance than epoxy-composite linings, and better impact resistance than ceramic linings. Pipes come in standard sizes and can also be custom made to your application.



### Standard Pipe Sizes

mm	Inch	OD	ID	Internal Hardfacing (mm)
63	2.5	73	52	3-5
75	3	89	72	3-6
90	3.5	102	86	3-6
100	4	114	98	3-8
150	6	168	150	3-8
200	8	219	197	4-9
250	10	273	249	4-9
300	12	324	297	4-9

Custom pipe sizes are also available, with multiple layers of hardfacing.

- Internally or externally hardfaced pipe
- Same composition as AbrasaPlate®
- All standard pipe sizes available
- Standard lengths up to 12m
- Smooth overlay
- Elbows, transitions and reducers
- Very small diameters
- Hardfaced joints, flanges or neck rings



# AVWELD

Leadership in Life Extension